

Product Catalog



Danau High Pressure Washers



Prices effective February 2024 **Prices Include GST**

\$699.00



High Pressure Washer -Cold Water - 2800PSI

Model: 3WA-2800B Displacement: 196cc Power: 6.5HP Loncin Type: OHV Pump Model: 3WA-3025A, Axial, Brass **Piston Plungers: With Ceramic Sleeves** Max. Pressure: 2800PSI, 193bar Max. Flow: 11.3lpm Nozzle Tips: 5 tips, QD Nozzle Hose ID and Length: 7.14mm x 10m Hose Type: Plastic Gun Type: Trigger Gun F00001 #2 Lance: 500mm (20") Frame Type: Folding Handle Wheel Size: 254mm (10") Pneumatic, Metal Rims **Detergent Injection: Yes Thermal Protection: Yes** Weight NW: 35kg



High Pressure Washer -Cold Water - 3600PSI

Model: 3WZ-3600JN Displacement: 390cc Power: 13HP Loncin Type: OHV Pump Model: 3WZ-1807A, Direct Drive Max. Pressure: 3600PSI, 248bar Max. Flow: 17lpm Nozzle Tips: 5 tips, QD Nozzle Hose ID and Length: 8mm x 10m Hose Type: Steel Braided Rubber Hose Gun Type: Trigger Gun F00001 #7 Lance: 500mm (20") Frame Type: Folding Handle Wheel Size: 330mm (13") Pneumatic, Metal Rims Detergent Injection: Yes Thermal Protection: Yes Pressure Gauge: Yes Weight NW: 41kg

\$1,249.00



High Pressure Washer - Cold Water -4000PSI

\$1,439.00

- Model: 3WZ-4000LC Displacement: 420cc Power: 14HP Loncin Type: OHV Pump Model: 3WZ-1807A Piston Plungers: With Ceramic Sleeves Max. Pressure: 4000PSI, 276bar Max. Flow: 18.2lpm Nozzle Tips: 5 tips, QD Nozzle Hose ID and Length: 8.0mm x 10m
- Hose Type: Steel Braided Rubber Hose Gun Type: Trigger Gun F00001 #2 Lance: 500mm (20") Frame Type: Folding Handle Wheel Size: 330mm (13") Pneumatic, Metal Rims Detergent Injection: Yes Thermal Protection: Yes Pressure Gauge: Yes Weight NW: 63kg



High Pressure Washer -Hot Water - 2600PSI

Model: DHC-18/11 DT- 90 Displacement: 212cc Power: 6.5HP Type: OHV, Electric Start Pump Model: DBC-1507A, Direct Drive Burner Type: DHB Burner Assy, 7.8L/h Max. Pressure: 2600PSI, 180bar Rated. Flow: 11lpm Max Temp: 100 Deg Nozzle Tips: 4 tips, QD Nozzle Hose ID and Length: 8mm x 15m Hose Type: Steel Braided, Hot Water, M22 Swivel Gun Type: Professional Trigger Gun with Insulated Lance Grip Wheel Size: 254mm (10") Solid, 100mm (4") Swivel Castor with Break **Detergent Injection: Yes**

Thermal Protection: Yes Weight: 130kg



\$249.00

High Pressure Pump -2800PSI

\$5,395.00

Model: 3WA-3025A Power Required: 6.5HP Input RPM: 3400 Max. Pressure: 2800PSI, 193bar Max. Flow: 11.3lpm Weight NW: 4kg

High Pressure Washer -Cold Water - 2200PSI

Model: 3WZ-1522-3S4 Pump Model: 3WZ-1512C, Triplex Max. Pressure: 2200PSI, 152bar Max. Flow: 9.22lpm Electric Motor: 3kw, electric cage Voltage and Hz: 230V, 50Hz RPM: 1450, 4 Pole Control Box: cable, control the on/off Plug and Cable: Yes, 10m Nozzle Tips: 5 tips, QD Nozzle Hose ID and Length: 7.14mm x 10m Hose Type: Plastic Gun Type: Trigger Gun Lance: 500mm (20") Frame Type: Wheel Moving Wheel Size: 254mm (10") Semi Pneumatic, Metal Rims Detergent Injection: Yes Thermal Protection: Yes Weight NW: 53kg



\$415.00

\$1,375.00

High Pressure Pump -3000PSI

Model: 3WZ-1507A Power Required: 7HP Input RPM: 3400 Max. Pressure: 3000PSI, 206bar Max. Flow: 12.6lpm Weight NW: 7kg





\$495.00

High Pressure Pump -3600PSI

Model: 3WZ-1807A Power Required: 13HP Input RPM: 3400 Max. Pressure: 3600PSI, 248bar Max. Flow: 18.21pm Weight NW: 9kg



\$21.95

6 in 1 Changeover Nozzle - Brass

Model: 6 in 1 Changeover Nozzle Brass Angle: 0, 15, 40, 25, Soap spray and rinse Material: Brass Max. Pressure: 3300psi Max. Temp.: 60 Degree C Orifice: 13.2lpm (3.5gpm)



Quick-coupler Spray Nozzle

Model: Nozzles (0,15,25,40) Body, 304 Stainless Steel and hardened Insert Inlet: 6.35mm (1/4") Plug Angle: 0, 15, 25, 40 Degree



\$12.95

Water Blaster Nozzle -Thread Type - 0 Degree Model: Nozzle - Thread Type - 0

Degree Max. Pressure: 4000psi (275bar) Max. Temp: 150 Degree C Orifice: 8 to 38lpm Nozzle Body: 304 S/S and hardened insert Thread Type: BSPT, 6.35mm.



\$23.95

Brass Turbo Nozzle -4000PSI

Model: 4000PSI Brass Turbo Nozzle Inlet: 6.35mm (1/4") Female Max. Temp.: 90°C Orifice: 2 Pieces 1.5gpm rate Colour: Black

\$49.95



\$19.95

6 in 1 Changeover Nozzle - Aluminium

Model: 6 in 1 Changeover Nozzle Aluminium Angle: 0, 15, 40, 25, Soap spray and rinse Material: Aluminium Max. Pressure: 3300psi Max. Temp.: 60 Degree C Orifice: 13.2lpm (3.5gpm)



\$12.95



\$12.95

Water Blaster Nozzle -Thread Type - 15 Degrees

Model: Nozzle - Thread Type - 15 Degrees Max. Pressure: 4000psi (275bar) Max. Temp: 150 Degree C Orifice: 8 to 381pm Nozzle Body: 304 S/S and hardened insert Thread Type: BSPT, 6.35mm.

Water Blaster Nozzle -Thread Type - 25 Degrees

Model: Nozzle - Thread Type - 25 Degrees Max. Pressure: 4000psi (275bar) Max. Temp: 150 Degree C Orifice: 8 to 38lpm Nozzle Body: 304 S/S and hardened insert Thread Type: BSPT, 6.35mm.



Plastic Surface Washer -381mm

\$145.00

Model: Plastic Surface Washer Diameter: 381mm (15") Heavy Duty Surface Washer Max. Pressure: 3000psi Max. Temp.: 60 Degree C Nozzle Orifice: 2 Pieces 5.71pm rate Colour: Black

Integrated rotating system with two 15 degree nozzles, the rotating spray increases the scrubbing to the cleaning process with a 13" cleaning path will quickly clean sidewalks, driveways, pool decks and parking lots. 10 times faster than a standard spray nozzle. 1/4" Quick disconnect for fast tip changes.



Stainless Steel Surface Washer - 610mm

Model: SURFACE CLEANER - 24IN Diameter: 610mm (24") Industrial Grade Surface Washer Max. Pressure: 4000psi Max. Temp.: 90 Degree C Nozzle Orifice: 2 Pieces 7.61pm rate (25 degree spray) Colour: Stainless Steel


Industrial Grade Rotating mechanism, dual bearing for maximum durability and life. Strengthened 304 Stainless Steel deck with strong-bristled brushers for long life and easy glide control. Large cleaning path allows easy 15 times faster than the standard wand and 10 times faster than the water broom. It can be used on decks, patio's, sidewalks, driveway, pool decks, parking lots and other flat services.



Water Blaster Nozzle -Thread Type - 40 Degrees

Model: Nozzle - Thread Type - 40 Degrees Max. Pressure: 4000psi (275bar) Max. Temp: 150 Degree C Orifice: 8 to 381pm Nozzle Body: 304 S/S and hardened insert Thread Type: BSPT, 6.35mm.

\$12.95



Pivoting Coupler

\$825.00

Model: Pivoting Coupler Angle: 120 Degree Inlet: 6.35mm (1/4") Plug Outlet: 6.35mm (1/4") QD Max. Pressure: 4000psi

Designed for use with pressure washers and offers versatile performance with 5 different cleaning angles to get hard to reach areas.

Adjusts 120 degrees for 5 different cleaning angles







\$395.00



\$425.00



\$625.00





Model: Hose Reel - 30m Mounting: Base Mounted Max. Pressure: 5000psi (345bar) Max. Temp: 60 Degree C Inlet / Outlet: 3/8" M x F Hose Included: 3/8" x 30m

Full Flow swivel brass joint with S/S shaft

Water Blaster Hose Reel - Pivoting - 30m

Model: Hose Reel - Pivoting - 30m Mounting: Pivoting Base Mounted Max. Pressure: 5000psi (345bar) Max. Temp: 60 Degree C Inlet / Outlet: 3/8" M x F Hose Included: 3/8" x 30m

Full Flow swivel brass joint with S/S shaft

Water Blaster Hose Reel - Pivoting - 50m

Model: Hose Reel - Pivoting - 50m Mounting: Pivoting Base Mounted Max. Pressure: 5000psi (345bar) Max. Temp: 60 Degree C Inlet / Outlet: 3/8" M x F Hose Included: 3/8" x 50m

Full Flow swivel brass joint with S/S shaft

Water Blaster Hose Reel - Pivoting - Right Angled Mounting - 30m

Model: Hose Reel - Pivoting - Right Angled Mounting - 30m Mounting: Pivoting Base Mounted Max. Pressure: 5000psi (345bar) Max. Temp: 60 Degree C Inlet / Outlet: 3/8" M x F Hose Included: 3/8" x 30m Full Flow swivel brass joint with S/S Shaft



\$445.00



\$64.95



Model: Hose Wheel - Self Winding -15m Mounting: Base Mounted Max. Pressure: 5000psi (345bar) Max. Temp: 60 Degree C Inlet / Outlet: 3/8" M x F Hose Included: 3/8" x 15 m Full Flow swivel brass joint with S/S

Thermal Plastic Hose -10m

Model: 10m Thermal Plastic Hose Material: Plastic Internal Diameter: 7.14mm (9/32") Fitting: 9.53mm (3/8") QD Max. Pressure: 3200psi Length: 10m

Steel Braided Rubber Hose - 10m

Model: 10m Steel Braided Rubber Hose Material: Rubber Internal Diameter: 8.0mm (5/16") Fitting: 9.53mm (3/8") QD Max. Pressure: 4310psi Length: 10m







\$229.00

Hose - 30m Model: 30m Steel Braided

Steel Braided Rubber

Rubber Hose Material: Rubber Internal Diameter: 8.0mm (5/16") Fitting: 9.53mm (3/8") QD Max. Pressure: 4310psi Length: 30m



\$69.95



\$145.00

杰/日

\$22.95

\$22.95

Sewer Cleaning Hose and Nozzle Kit - 15m

Model: Sewer Hose Max 3000PIS + Nozzle 15m Material: 5mm (1/5") Thermoplastic Hose Fitting: M22 Fitting and Jetting Nozzle Max. Pressure: 3000psi Max. Temp: 60 Degree C Length: 15m

Steel Braided Rubber Hose - Hot Water - 15m Braided Hose - 15m

Model: 15M Steel Braided Hose—HW Material: Steel Braided Rubberised Fabric

Internal Diameter: 8.0mm (5/16") Fitting: 9.53mm (3/8") QD Max. Pressure: 3200psi Max. Temp.: 150 Degree C Length: 15m

Hour Meter - Petrol or

Model: Hour Meter - Petrol or

Casing: 100% epoxy encapsu-

Diesel Motors

Diesel Motors

Resists Water

lated



Waster Blaster - Water Broom - 305mm (12")

Model: Water Broom - 305mm Max. Pressure: 4000psi (275bar) Max. Temp: 60 Degree C Nozzle Orifice: 3 pieces, 7.6lpm (2gpm)

Features 3 fixed spray tips which are mounted on an Aluminium bar, making cleaning of any flat surfaces faster. Swivel wheels holds broom at optimum distance from cleaning surface making it effortless to control in any direction. 1/4" Quick disconnect for fast tip changes.

\$74.95

Waster Blaster - Water Broom - 406mm (16")

Model: Water Broom - 406mm Max. Pressure: 4000psi (275bar) Max. Temp: 60 Degree C Nozzle Orifice: 4 pieces, 7.6lpm (2gpm)

Features 4 fixed spray tips which are mounted on an Aluminium bar, making cleaning of any flat surfaces faster. Swivel wheels holds broom at optimum distance from cleaning surface making it effortless to control in any direction. 1/4" Quick disconnect for fast tip changes.

\$84.95





Water Blaster - Flow Control

Model: Water Blaster - Flow Control Inlet/Outlet: M22 x M22 Swival Max. Temp 60 Degree C Flow: 151pm (4.0gpm)

Connects between the trigger gun and wand, saves having to go to the pump for pressure control.

¢ 0





High Pressure Heavy Duty Gun Assembly - 3600PSI

Model: F00001 #2 Gun Assy Inlet: 9.53mm (3/8") Plug Outlet: 6.35mm (1/4") QD Flow: 30lpm (8gpm) Max. Temp.: 60 Degree C Max. Pressure: 3600psi Valve: Brass Connection Tube: Stainless Steel Wand: 508mm (20") Stainless Steel

\$59.95

\$34.95

High Pressure Professional Gun Assembly - 5000PSI

Model: F00001 #7 Gun Assy Inlet: 9.53mm (3/8") Plug Outlet: 6.35mm (1/4") QD Flow: 40lpm (10.5gpm) Max. Temp.: 90 Degree C Max. Pressure: 5000psi Valve: Brass Connection Tube: Stainless Steel Wand: 508mm (20") Stainless Steel

\$64.95



Detergent Injection Hose

\$8.95

Model: 3WZ-4000lcdetergenti Length: 1.5M

Use for either with a built in detergent tank or with a separate bottle of detergent, replacement for most pressure washers

PVC detergent hose with plastic filter with weight

Pressure Gauge - 8700PSI

Model: Gauge PSI and Bar 0-600bar Max. Pressure: 8700psi (600bar)

For 3WZ-4000LC High Pressure Washer



High Pressure Dual Wand -4000PSI

\$99.00

Model: Dual Wand + F00001 #7 GUN ASSY Max. Pressure: 4000psi Connection: M22 Length: 1235mm

Bolt on vented plastic insulated grip for good protection, brass high-low switch valve with handle for quick change over and better holding. Seamed stainless steel or seamed plated steel lance. M22 male for connect to gun, pre-fit with brass soap nozzle and 6.35mm (1/4") QD for nozzle tips build with nozzle protector.



High Pressure Telescopic Wand - 4000PSI

Model: Telescopic Wand Material: Aluminium Telescopic Poles Inlet: 9.53mm (3/8") Plug Outlet: 9.53mm (3/8") QD Flow: 40lpm (10.5gpm) Max. Temp.: 60 Degree C Max. Pressure: 4000psi Length: 5486mm (18ft)

\$185.00

High Pressure Telescopic Wand - Belt

Model: Belt for Telescopic Wand Material: Durable Nylon

\$11.95



Model: Foam Generator Inlet: 1/4" Plug Max. Temp 60 Degree C Max. Pressure: 4000psi

Simply attach to the pressure gun, the detergent will pick up by the high pressure flow and mix with air through the foaming system and create the thick mousse style clinging foam, softening the soil in time and making it easy to



remove when rinsing the car. For the dusty or lightly dirty vehicles, that it doesn't require you to touch the vehicle which could rub dirt against the paint. Simply spray over the vehicle and leave the foam to dwell soaking up the dirt in the process, rinse and dry leaving an excellent finish.

Variable angle spray pattern nozzle and chemical adjustable to control the amount of foam.

\$44.95





Water Blaster -Adapter 3/8" QD to ZG3/8" Female

Model: 3/8"QD TO ZG3/8" FEMALE Connector Type: 3/8" Quick Connect to ZG 3/8" Female thread

\$5.95

Water Blaster -Adapter 3/8" Plug to ZG3/8" Female

Model: 3/8"PLUG TO ZG3/8" FEMALE Connector Type: 3/8" Plug to ZG 3/8" Female thread

\$13.95



Water Blaster -Adapter 3/8" QD to M22 Female

Model: 3/8"QD TO M22 FEMALE Connector Type: 3/8" Quick Connect to M22 Female thread



\$5.95

Water Blaster -Adapter 3/8" Plug to M22 Male

Model: 3/8"PLUG TO M22 MALE Connector Type: 3/8" Plug to M22 Male thread

\$13.95



Water Blaster -Adapter 3/8"QD to M22 Male

Model: 3/8"QD TO M22 MALE Connector Type: 3/8" Quick Connect to M22 Male thread

\$14.95



\$15.95

Water Blaster -Adapter 3/8" Plug to M22 Female

Model: 3/8" PLUG TO M22 FEMALE Thread Size: M22 x 14mm (internal) Connector Type: 3/8" Plug to M22 Female thread





CONTACT US

Phone: (03) 313 1415

Email: Sales@GoodsDirect2U.co.nz

Web: www.GoodsDirect2U.co.nz

Address: 589 Mount Thomas Road, RD1, Fernside, New Zealand 7471

Opening Hours:

9am - 5pm Monday-Friday 10am - 12noon Saturday