



Product Catalog



***Transfer Tanks and
Accessories***



Prices effective

June 2023

Prices Include GST

≡ Transfer Tanks and Accessories



Diesel Transfer Tank with Pump, 12V, 40LPM - 100L

\$795.00

Model: DD100
Volume: 100L
Power: 280W
Voltage: 12VDC
Current: 22A
Maximum Operating Time: 30min
RPM: 2600
Flow (LPM): 40
Outlet Hose Size: 19.05mm (3/4")
Priming: Self Priming
Hose Length: 4m
Power Cord Length: 4m
Size: 800(L) x 757(W) x 450(H)mm
Weight NW: 23Kg

Includes:
 Battery Clamps

Features:
 High quality trigger nozzle swivel with automatic cut off.
 Safety internal pump bypass
 Tank made from impact resistant polyethylene UV stabilized
 Highly durable pad lockable cover
 Internal suction foot filter
 Heavy duty battery clamps with inline fuse

Suitable for Diesel only



Diesel Transfer Tank with Pump, 12V, 40LPM - 200L

\$895.00

Model: DD200
Volume: 200L
Power: 280W
Voltage: 12VDC
Current: 22A
Maximum Operating Time: 30min
RPM: 2600
Flow (LPM): 40
Outlet Hose Size: 19.05mm (3/4")
Priming: Self Priming
Hose Length: 4m
Power Cord Length: 4m
Size: 1050(L) x 747(W) x 570(H)mm
Weight NW: 35.8Kg

Includes:
 Battery Clamps

Features:
 High quality trigger nozzle swivel with automatic cut off.
 Safety internal pump bypass
 Tank made from impact resistant polyethylene UV stabilized
 Highly durable pad lockable cover
 Internal suction foot filter
 Heavy duty battery clamps with inline fuse

Suitable for Diesel only.



Diesel Transfer Tank with Pump, 12V, 40LPM - 500L

\$1,435.00

Model: DD500
 Volume: 500L
 Power: 280W
 Voltage: 12VDC
 Current: 22A
 Maximum Operating Time: 30min
 RPM: 2600
 Flow (LPM): 40
 Outlet Hose Size: 19.05mm (3/4")
 Priming: Self Priming
 Hose Length: 4m
 Power Cord Length: 4m
 Size: 1720(L) x 760(W) x 760(H)mm
 Weight NW: 57.6Kg

Includes:
 Battery Clamps

Features:
 High quality trigger nozzle swivel with automatic cut off.
 Safety internal pump bypass
 Tank made from impact resistant polyethylene UV stabilized
 Highly durable pad lockable cover
 Internal suction foot filter
 Heavy duty battery clamps with inline fuse.

Suitable for Diesel only



Diesel Transfer Tank with Pump, 12V, 56LPM - 1000L

\$3,495.00

Model: DD980
 Volume: 1000L
 Power: 450W
 Voltage: 12VDC
 Current: 15A
 Maximum Operating Time: 30min
 RPM: 2800/3400
 Flow (LPM): 56
 Outlet Hose Size: 19.05mm (3/4")
 Priming: Self Priming
 Hose Length: 10m
 Power Cord Length: 6m
 Size: 1100(L) x 1300(W) x 1200(H)mm
 Weight NW: 128Kg

Includes:
 Battery Clamps

Features:
 High quality trigger nozzle swivel with automatic cut off.
 Safety internal pump bypass
 Tank made from impact resistant polyethylene UV stabilized
 Highly durable pad lockable cover
 Internal suction foot filter
 Heavy duty battery clamps with inline fuse.
 Water Separator Filter
 Led Lid Light
 Diesel Level Gauge
 Retractable Hose Reel

Suitable for Diesel only

≡ Transfer Tanks and Accessories



Adblue Transfer Tank with Pump, 12V, 26LPM - 400L

\$1,595.00

Model: AD400
 Volume: 400L
 Power: 240W
 Voltage: 12VDC
 Current: 10A
 Maximum Operating Time: 30min
 RPM: 2900
 Flow (LPM): 26
 Outlet Hose Size: 19.05mm (3/4")
 Priming: Self Priming
 Hose Length: 4m
 Power Cord Length: 4m
 Size: 1100(L) x 640(W) x 610(H)mm
 Weight NW: 49Kg

Includes:
 Battery Clamps

Features:
 High quality trigger nozzle swivel with automatic cut off.
 Tank made from impact resistant polyethylene UV stabilized
 Highly durable pad lockable cover
 Internal suction foot filter
 Heavy duty battery clamps with inline fuse

Suitable for Diesel Exhaust Fluid (AdBlue) only



Diesel Transfer Pump - 12V, 40LPM

\$225.00

Model: DP40012K
 Power: 180W
 Voltage: 12VDC
 Current: 15A
 Maximum Operating Time: 30min
 RPM: 4300
 Flow (LPM): 40
 Outlet Hose Size: 19.05mm (3/4")
 Priming: Self Priming
 Hose Length: 2m
 Power Cord Length: 2m

Includes:
 Battery Clamps
 Internal suction foot filter
 Mounting Bracket

Suitable for Diesel only



**Diesel Transfer Pump -
12V, 40LPM**

\$249.00

*Model: DP40012K-N
Power: 180W
Voltage: 12VDC
Current: 15A
Maximum Operating Time: 30min
RPM: 4300
Flow (LPM): 40
Outlet Hose Size: 19.05mm (3/4")
Priming: Self Priming
Hose Length: 2m
Power Cord Length: 2m*

*Includes:
Battery Clamps
Internal suction foot filter
Mounting Bracket*

Suitable for Diesel only



**Fuel Nozzle - 73PSI -
19.05mm (3/4")**

\$39.95

*Model: J60 Nozzle
Maximum Flow (LPM): 60
Maximum Pressure: 72.5PSI / 5Bar
Outlet Hose Size: 19.05mm (3/4")*

Features:

*Made of high quality aluminium
Trigger Lock*

≡ Transfer Tanks and Accessories



**Fuel Nozzle - Auto Shut Off,
Flow Sensor - 60PSI -
19.05mm(3/4")**

\$199.00

Model: NW01-A
Maximum Flow (LPM): 120
Maximum Pressure: 290PSI / 20Bar
Outlet Hose Size: 19.05mm (3/4")
Standby Battery Time: ~2 Years
Single Fuel Count: 0-9999L
Accumulated Fuel Count: 0-999999
Units: L / GAL / PTS / QTS
IP Rating: 54

Features:

Made of high quality aluminium
Measures flow rate, single use fuel count & total use fuel count.
Swivel Fitting
Trigger Lock
Auto Shut Off
Suitable for Diesel, Urea, Kerosene, Chemicals, Petrol



**Adblue Nozzle -Auto Shut
Off, Flow Sensor - 51PSI -
19.05mm (3/4")**

\$295.00

Model: AD13PP
Maximum Flow (LPM): 30
Maximum Pressure: 60PSI / 3 Bar
Outlet Hose Size: 19.05mm (3/4")
Standby Battery Time: ~2 Years
Single Fuel Count: 0-9999L
Accumulated Fuel Count: 0-999999
Units: L / GAL / PTS
IP Rating: 54

Includes: 2 Nozzle Low Flow (10Lpm) & High Flow 30(Lpm)

Features:

Measures flow rate, single use AdBlue count & total use Ad-Blue count.
Trigger Lock
Auto Shut Off
Suitable for Diesel Exhaust Fluid (AdBlue) only



CONTACT US

Phone: 03 313 1415

Fax: 03 313 1495

Email: sales@GoodsDirect2U.co.nz

Web: [www. GoodsDirect2U.co.nz](http://www.GoodsDirect2U.co.nz)

Address: 589 Mount Thomas Road,
RD1,
Fernside
New Zealand

Opening Hours: 9am - 5:00pm Mon-Fri
10am - 12am Sat.
